

### Main

Range of product	Terminal blocks
Product or component type	Terminal block
Technology type	Screw technology
Terminal block type	Passthrough
Fixing mode	Clip-on (35 mm asymmetrical rail) Clip-on (35 mm notched symmetrical rail) Clip-on (35 mm symmetrical DIN rail)
Nominal cross section	10 mm <sup>2</sup>
Length	51 mm
Colour	Grey
Number of points	2
Sale per indivisible quantity	50


### Complementary

Width	10 mm
Height	55 Mm on 35 mm symmetrical DIN rail 59.5 Mm on 35 mm asymmetrical rail 62.5 mm on 35 mm notched symmetrical rail
Cable cross section	2.5...10 Mm <sup>2</sup> , flexible cable with or without cable end 6...16 mm <sup>2</sup> , solid cable
Tightening torque	2...2.5 N.M, M3.5 conforming to EN 60999 2...2.5 N.m, M3.5 conforming to IEC 60974-1
[Ue] rated operational voltage	500 V AC/DC conforming to UTE category C 750 V conforming to ATEX Exe II Ex II 2 GD 750 V AC conforming to VDE group C 800 V conforming to EN/IEC 60947-7-1 900 V DC conforming to VDE group C 600 V, AWG 16...AWG 6 CSA 600 V, AWG 16...AWG 6 UL
[In] rated current	65 A, AWG 16...AWG 6 UL[RETURN]70 A, AWG 16...AWG 6 CSA[RETURN]3... 57 A conforming to EN/IEC 60947-7-1[RETURN]43...56 A conforming to ATEX Exe II Ex II 2 GD[RETURN]63 A conforming to VDE group C
Material	Copper or brass: commoning link Polyamide 6.6: insulating case Zinc chromed steel: connector and screw
Dielectric loss	0.01 at 1 MHz conforming to IEC 60250 0.01 at 1 MHz conforming to VDE 0303-T4
Dielectric constant	3.7 at 1 MHz
Resistivity	Conforming to IEC 60093 Conforming to VDE 0303-T30
Surface resistance	10 GΩ conforming to IEC 60093 10 GΩ conforming to VDE 0303-T30
Creep resistance	500 CTI (> 400 kB) conforming to IEC 60093 500 CTI (> 400 kB) conforming to VDE 0303-T30
Flame retardance	V0, thickness 0.8 mm conforming to UL 94
Net weight	26 g

## Environment

Dielectric test voltage	8 kV conforming to EN/IEC 60947-7-1
Product certifications	LR[RETURN]ASEV[RETURN]ATEX[RETURN]CSA[RETURN]VDE[RETURN]UL-Ex[RETURN]CSA-Ex[RETURN]UL[RETURN]UL-Aex[RETURN]GL[RETURN]DNV
Dielectric strength	80 kV conforming to IEC 60243-1 80 kV conforming to VDE 0303-T21
Ambient air temperature for operation	-40...130 °C conforming to IEC 60216-1 -40...130 °C conforming to VDE 0304-T21

## Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a>
-------------------	--

## Contractual warranty

Warranty	18 months
----------	-----------