

in-line fuse switch-disconnector 630 A (33 723)



Description

Article

Part No.: 33 723

QUADRON[®] 185Power

in-line fuse switch-disconnector 630 A

Bolt M12, 3-pole switchable, with fuse monitoring
size 3

for busbars 30, 40, 60, 80, 100, 120 x 10

System

185Power

Product group 12

Subgroup 55

pack size 1

EAN 4021267337230

Advantages of the product

Self-closing inspection holes are available in the cover.

Cover can be locked when closed.

Catalog page 2015 : 4/7, 4/8

eCl@ss 6.1 27142108
eCl@ss 7.1 27142108
ETIM 4.0 EC001040
ETIM 5.0 EC001040

Approvals

Standards

IEC 60947-1:2007 + A1:2010 + A2:2014
IEC 60947-3:2008 + A1:2012

Approvals

IEC (CB), CCC



Type number: QU185-3

CCC certificate: 2015010302773479

Product data

Electrical data

Rated current (IEC): 630 A
Rated voltage (IEC) AC: 400 V

Utilisation category AC (IEC 60947-3): AC-23B 630A/400V
AC-22B 630A/500V
AC-21B 500A/690V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 75.5 W.
(The power dissipation for operation with rated current would be 118 W.)

rated isolation voltage U_i (AC): 800
V
Rated surge voltage U_{imp} : 4 kV
max. permitted voltage (IEC) AC: 500
V
max. permitted voltage (IEC) DC: 250
V

cond. rated short-circuit current with fuses: 80 kA / 690 V
100 kA / 500 V

approved with fuse links of characteristics: gG

for fuse links IEC 60269-2-1 (I) / DIN VDE 0636-201 size 3 up to 48W power dissipation

Special operating conditions corresponding to IEC / EN 61439-1 may yield to faulty activations of pilot switches and fuse monitors. The operating conditions have to be considered for the analysis of status signals.

Degree of protection IP20 at front (see mounting instruction)

Mechanical data

W x H x D: 99 x 670 x 189
Weight: 576.1 kg/100
for busbars: 30, 40, 60, 80, 100, 120 x 10

front degree of protection: IP20

Type of fastening:

can be screwed onto drilled busbar, diameter 13mm, undrilled mounting with terminal clamp connection:

screw connection M12

Terminal points

screw M12 :

Md 30 Nm

Material properties

Main body:	temperature stability 130°C, self-extinguishing in acc. to UL 94, creepage resistance CTI 600, halogen-free
Contacts:	spring-loaded copper contacts, silver plated
Shock protection cover:	temperature stability 125°C, self-extinguishing in acc. to UL 94, creepage resistance CTI 200, halogen-free
Handle:	temperature stability 125°C, self-extinguishing in acc. to UL 94, creepage resistance CTI 600, halogen-free
Connecting screws:	screw M12, galvanized, chromized

Reference

Always use connection cover 33733 for connection top and for using cable lugs.

Accessories



33 736
Box terminal
for Cu and Al 70mm² – 300mm²
size 1-3



33 733
Terminal compartment cover
universal for NH-rails size 1-3 and connection rail 800A
size 1- 3



33 738
Terminal clamp for QUADRON®185Power
for busbar systems with CrossLink touch-safe protection
size 1 - 3



33 740
Terminal clamp for QUADRON®185Power
for systems without touch-safe protection
size 1 - 3



33 746
Current transformer 250 A / 5 A
2,5 VA / class 1
size 1 - 3



33 747
Current transformer 400 A / 5 A
2,5 VA / class 1
size 1 - 3

wöhner

33 748

Current transformer 600 A / 5 A
2,5 VA / class 1
size 1 - 3



33 156

pilot switch
changeover 250 V AC / 5 A; 30 V DC / 4 A



33 758

lateral bearing strip
for front covers
size 00 - 3

wöhner

33 744

Current transformer 150 A / 5 A
1,5 VA / class 1
size 00 - 3

wöhner

33 745

Current transformer 200 A / 5 A
1,5 VA / class 1
size 1 - 3

wöhner

33 753

Current transformer 150 A / 5 A
1,5 VA / class 0,5
size 00 - 3

wöhner

33 754

Current transformer 150 A / 5 A, with declaration of conformity
1,5 VA / class 0,5
size 00 - 3

wöhner

33 761

Rear touch-safe protection cover
Rear protection for Phase L1
NEW

wöhner

33 292

Current transformer 200 A / 5 A
1,5 VA / class 0,5
size 00 - 3

wöhner

33 293

Current transformer 200 A / 5 A, with declaration of conformity
1,5 VA / class 0,5
size 1 - 3

wöhner

33 294

Current transformer 250 A / 5 A
2,5 VA / class 0,5
size 1 - 3

wöhner

33 295

Current transformer 250 A / 5 A, with declaration of conformity
2,5 VA / class 0,5
size 00 - 3

wöhner

33 298

Current transformer 400 A / 5 A
2,5 VA / class 0,5
size 00 - 3

wöhner

33 299

Current transformer 400 A / 5 A, with declaration of conformity
2,5 VA / class 0,5
size 00 - 3

wöhner

33 762

Universal current transformer module
for mounting in the connection compartment, including front and rear cover
size 1 - 3

NEW