



**Part No.: 02538**  
**Main branch terminal 35 mm<sup>2</sup>**  
**5-pole, type "A"**

Incoming terminals 2x 35 mm<sup>2</sup>, 5x 2 outgoing terminals 25 mm<sup>2</sup>

**Standards :**  
DIN VDE 0603-2/03.98

**Electrical Data :**  
500 V

**Mechanical Data :**  
Width x Height x Depth (mm): 192 x 60 x 46  
Weight (g): 503  
clip-on, for horizontal and vertical mounting

**Connections :**  
incoming screw M8 :  
16 - 35 mm<sup>2</sup>, solid and stranded round cables,  
10 - 25 mm<sup>2</sup>, flexible cables, with wire-end ferrule,  
Md 4 Nm

outgoing screw M6 :  
10 - 25 mm<sup>2</sup>, solid and stranded round cables,  
6 - 16 mm<sup>2</sup>, flexible cables, with wire-end ferrule,  
Md 3 Nm

**Material Characteristics :**  
Main body:  
temperature stability 125°C,  
self-extinguishing in acc. to UL 94,  
creepage resistance CTI 200,  
halogen-free

Wöhner reserves the right to make modifications to its components, as the result of developments and technical advances.

**Material Characteristics :**

Ingoing terminal:

+/- (PZ3), galvanized, chromized

Outgoing terminal:

+/- (PZ2), galvanized, chromized

Terminal body:

brass

**Remarks :**

Each terminal connection has two terminal screws for reliable contacting.

**Accessories to Article 02538 :**

78491 cover section

1 m long, for main branch terminals