


NH bus-mounting fuse base, 160 A (03 370)



Description

Article

Part No.: 03 370

QUADRON® 60Classic

NH bus-mounting fuse base, 160 A

screw

size 00 / 1P

System

60Classic

100Energy

185mm-System

Product group 10

Subgroup 27

pack size 10

EAN 4021267033705

Catalog page 2015 : 3/3

eCl@ss 6.1 27142106
eCl@ss 7.1 27142106
ETIM 4.0 EC000067
ETIM 5.0 EC000067

Approvals

Standards

IEC 60269-1:2006 + A1:2009 + A2:2014
IEC 60269-2:2013

Approvals

Germanischer Lloyd



Product data

Electrical data

Rated current (IEC): 160 A
Rated voltage (IEC) AC: 690 V
Rated voltage (IEC) DC: 440 V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 3 W.
(The power dissipation for operation with rated current would be 4.7 W.)

rated isolation voltage U_i (AC): 800 V
Rated surge voltage U_{imp} : 6 kV
max. permitted voltage (IEC) AC: 1000 V
max. permitted voltage (IEC) DC: 1000 V

breaking capacity with fuses: 50 kA

for fuse links IEC 60269-2 / DIN VDE 0636-201 size 00 up to 12W power dissipation

Mechanical data

W x H x D: 35 x 102 x 86

Weight: 14.2 kg/100

Poles: 1-pole

Type of fastening: hook clips, screw connection M8, 12 - 14Nm torque

Terminal points

NHUT_SCHRAUBE_M8


Material properties

Main body: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 600,
halogen-free

Contacts: spring-loaded copper contacts, silver plated

Connecting screws: screw M8, galvanized, chromized


Accessories



03 161
knife link 160 A
size 00



03 502
NH fuse extractor handle
open
size 000 - 3



03 791
shock protection in two parts
for NH fuse-base
size 00